

## COAXIAL ATTENUATORS (Model # : ACAT SERIES)



### Description

- LOW ATTENUATION VARIATION
- LOW VSWR

ACAT series is a fixed value attenuator. Standard attenuation values of the models are 3, 6, 10, 15, 20, 30 and 40dB. Other values and connectors are available

upon request

### Specifications

Model No.	ACAT-3000SSM-3	ACAT-3000SSM-6	ACAT-3000SSM-10	ACAT-3000NNM-15	ACAT-3000NNM-30	ACAT-3000SSM-15	ACAT-3000SSM-30
Frequency Range	DC ~ 3 GHz	DC ~ 3 GHz	DC ~ 3 GHz	DC ~ 3 GHz	DC ~ 3 GHz	DC ~ 3 GHz	DC ~ 3 GHz
Attenuation	3 dB	6 dB	10 dB	15 dB	30 dB	15 dB	30 dB
VSWR	1.20:1max.	1.20:1max.	1.20:1max.	1.20:1max.	1.20:1max.	1.20:1max.	1.20:1max.
Power Rating	1 W max.	1 W max.	1 W max.	1 W max.	1 W max.	1 W max.	1 W max.
Dimension(WxLxH) [mm(inch)]	27x18x15 (1.06x0.71x0.59)			21x26x20 (0.83x1.02x0.79)		19x22.5x12 (0.75x0.89x0.47)	

\* The specification can be modified upon buyer's requests.

\* All specifications are subject to change without notice.

\* The latest specifications are available at [www.actipass.com](http://www.actipass.com)

**Actipass Co., Ltd.**

451, Hagal-Dong, Giheung-Gu, Yongin-Si, Kyunggi-Do, Korea

TEL : 82-31-201-7589 FAX : 82-31-204-7502

E-Mail : [steve@actipass.com](mailto:steve@actipass.com) / actipass@actipass.com www.actipass.com



Plotting Chart

