

**Actipass Co., Ltd.**

451, Hagal-Dong, Giheung-Gu, Yongin-Si, Kyunggi-Do, Korea

TEL : 82-31-201-7589 FAX : 82-31-204-7502

E-Mail : [steve@actipass.com](mailto:steve@actipass.com) / actipass@actipass.com www.actipass.com

## BANDPASS FILTER FOR CDMA RECEIVER (Model # : ACF-C820)

**Description**

- DESIGNED FOR CELLULAR BASESTATION
- LOW COST
- SHORT DELIVERY

**Specifications**

Model No.	ACF-C820
Passband	824 MHz - 849 MHz
Bandwidth	25 MHz
Insertion Loss	Max. 1.0 dB
Flatness in Full Band	±0.3 dB
Group Delay	Max. 20 ns at Passband
Return Loss	18 dB min.
Maximum power Input	500 Watts
Coupling Value	30 ± 1 dB
Connector Type(I/O)	Type-N (Female)
Coupling Port	TNC (Female)
Temperature	-30 °C to +60 °C
Material	Al
Dimension	265mm X 112mm X 32mm
Weight	980 gram

\* The specification can be modified upon buyer's requests.

\* All specifications are subject to change without notice.

\* The latest specifications are available at [www.actipass.com](http://www.actipass.com)