



POWER TERMINATIONS (Model # : APT SERIES)

 Description



The APT series is designed to have a low VSWR to high power application. These terminations will handle from 30 to 120 watts continuous power. Typical VSWR is 1.2. These can be derated for flange temperatures up to 150°C (see power de rating chart)


 Specifications

| Model No. | APT-30 | APT-60 | APT-120 | APT-150 |
|--------------------------------|-----------------------------------|--------------------------------|---------------------------------|---------------------------------|
| Frequency Range | DC ~ 2.0 GHz | DC ~ 2.0 GHz | DC ~ 2.0 GHz | DC ~ 2.0 GHz |
| VSWR | 1.20:1max. | 1.20:1max. | 1.20:1max. | 1.20:1max. |
| Impedance | 50 ohm | 50 hm W | 50 hm | 50 hm |
| Average Power | 30 W | 60W | 120 W | 150 W |
| Peak Power | 2 kW | 2 kW | 2 kW | 2 kW |
| Dimension(WxLxH) [mm(inch)] | 100x49.5x76.5 (3.94x1.95x3.01) | 115x100x78 (4.53x3.94x3.07) | 200x120x140 (7.88x4.73x5.51) | 100x128x116 (3.94x5.04x4.57) |

* The specification can be modified upon buyer's requests.

* All specifications are subject to change without notice.

* The latest specifications are available at www.actipass.com

 Plotting Chart

