

Actipass Co., Ltd.

451, Hagal-Dong, Giheung-Gu, Yongin-Si, Kyunggi-Do, Korea

TEL : 82-31-201-7589 FAX : 82-31-204-7502

E-Mail : steve@actipass.com / actipass@actipass.com www.actipass.com

DAB ANTENNA FOR SINGLE INPUT RECEIVER



Description

This is a high performance antenna designed specifically for single input satellite radio receivers in USA. Its low-profile, easy-to-install design, maximizes installation options and usability. This antenna is designed to fit with the progressive styling of today's vehicles.

- Easy Installation.
- High Performance Antenna
- Compact Size.
- Low Cost.

Specifications

	AAS-2320/12.5-LCL-XX	
	TERRESTRIAL	SATELLITE
Frequency Range	2320 ~ 2332.5 MHz	
Antenna Gain	1 dBi	2 dBic
Impedance	50 Ohm	
Azimuth	Omni directional	
Polarization	Linear Vertical	LHCP(Circular)
LNA Gain	17 dB min.	30 dB min.
LNA Noise Figure	2 dB max.	0.9 dB max.
Current Drain	100 mA	
Cable	4 meters	
Connector	SMB	
Operating Temperature	-40 ~ +85°C	

* The specification can be modified upon buyer's requests.

* All specifications are subject to change without notice.

* The latest specifications are available at www.actipass.com