

Actipass Co., Ltd.

451, Hagal-Dong, Giheung-Gu, Yongin-Si, Kyunggi-Do, Korea

TEL : 82-31-201-7589 FAX : 82-31-204-7502

E-Mail : steve@actipass.com / actipass@actipass.com www.actipass.com

NARROW-WALL DIRECTIONAL COUPLERS (Model # : AWNC SERIES)



▣ Description

- AVAILABLE WITH 3 OR 4 PORT
- FULL BAND WIDTH
- MEAN COUPLING: 10 dB, 20 dB, 30 dB, 40 ± 0.5 dB
- VAR FROM MEAN COUPLING vs FREQ.: ± 1.5 dB
- LOW LOSS & VSWR

The AWNC series are especially ideally suited to for systems application because of their mechanical simplicity and high-power handling capabilities. Typical directivity is better than 25dB. Special multi-port couplers can be also available upon request.

▣ Specifications

Model No.	Frequency Range	Waveguide		VSWR	Directivity
		WR*	RG**		
AWBC-284	2.60 - 3.95 GHz	284	75/U	1.15:1 max.	23 dB min.
AWBC-229	3.30 - 4.90 GHz	229	341/U	1.15:1 max.	23 dB min.
AWBC-187	3.95 - 5.85 GHz	187	95/U	1.15:1 max.	23 dB min.
AWBC-159	4.90 - 7.05 GHz	159	344/U	1.15:1 max.	23 dB min.
AWBC-137	5.85 - 8.20 GHz	137	106/U	1.15:1 max.	23 dB min.
AWBC-112	7.05 - 10.0 GHz	112	68/U	1.15:1 max.	23 dB min.
AWBC-90	8.20 - 12.4 GHz	90	67/U	1.15:1 max.	23 dB min.
AWBC-75	10.0 - 15.0 GHz	75	347/U	1.15:1 max.	23 dB min.

* The specification can be modified upon buyer's requests.

* All specifications are subject to change without notice.

* The latest specifications are available at www.actipass.com